

PROTAC® RAIL MOUNT 1 DEDICATED FIXED-MOUNT LONG GUN LIGHT



Case Material/Lens: 6000 Series machined aircraft aluminum with anodized finish. High temperature, shock mounted, AR coated, impact resistant BOROFLOAT® glass lens

Dimensions/ Length: 4.25 in. (10.8 cm) Width: 1.20 in. (3.04 cm) Height: 1.50 in. (3.81 cm)
Weight: 4.3 oz (121.9 grams) with CR123 battery; 4.5 oz (127.5 grams) with AA alkaline

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime; TIR optic produces a concentrated beam with optimum peripheral illumination

On/Off: Multi-function, push-button tactical tail switch or Dual remote pressure switch with latching push button. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe (factory default), high only, or low/high

Output/Run time: CR123A lithium battery output:

- High for bright light: 350 lumens; 12,000 candela; 219m beam; runs 1.75 hours
- Low for longer run time: 40 lumens; 1,380 candela; 19m beam; runs 14.5 hours

AA alkaline/AA lithium battery output:

- High: 150 lumens; 4,950 candela; 141m beam; runs 1.5 hours (alkaline); runs 4.5 hours (AA lithium)
- Low: 40 lumens; 1,380 candela; 19m beam; runs 8 hours (alkaline); runs 14 hours (AA lithium)

Strobe for signaling or disorienting

Battery: **Dual fuel** - uses 1 AA alkaline or CR123A lithium battery (both included); also accepts AA lithium

- Features:
- Remote pressure switch features momentary and "constant on" operation
 - Fixed rail grabber with thumbscrew easily attaches to Picatinny rails (no tools required)
 - One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching.
 - Securely fits a broad range of weapons; mounts directly to guns with MIL-STD-1913 (Picatinny) rails
 - Operating temperature: -40°F to +120°F
 - IPX7 waterproof to 1 meter for 30 minutes (with standard button switch)
 - IPX4 water-resistant (with remote pressure switch)
 - Includes remote pressure switch, push-button tailcap switch, remote retaining clips, double-sided tape and zip ties

Approvals: Meets applicable European Community directives

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit www.streamlight.com for full warranty information.

Item	UPC	Part #
ProTac Rail Mount 1	080926-88058-0	88058
Remote Retaining Clips	080926-88178-5	88178
Lithium Batteries 2 Pack	080926-85175-7	85175
Lithium Batteries 6 Pack	080926-85180-1	85180
Lithium Batteries 12 Pack	080926-85177-1	85177
Lithium Batteries 400 Pack	080926-85179-5	85179

Made in China

