

PROTAC® RAIL MOUNT VIR PRO

MULTI-FUEL, WHITE LIGHT AND IR LONG GUN LIGHT



Jack-Cap® offers operational switch redundancy



Mode selector switch for easy section of IR/Off/White light



Features White LED and 940nm IR LED



Available Colors: 

ProTac® Rail Mount VIR Pro delivers both visible white light and IR illumination, easily selectable via a head-mounted switch. An integrated cutoff prevents accidental activation of visible light while in IR mode. Its Jack-Cap® provides switch redundancy, supporting both push-button and remote pressure switch operation. Its rail clamp securely mounts to MIL-STD-1913 rails and includes an M-LOK® adapter for compatibility with M-LOK® and M-LOK®-compatible systems.

OUTPUT

	HIGH	MEDIUM	LOW	IR HIGH	IR LOW
LUMENS	1,100	540	120	2,300mW	600mW
CANDELA	40,000	19,000	4,200	---	---
DISTANCE	400m	276m	130m	---	---
RUN TIME <small>SL-B26</small>	2 hrs	3.75 hrs	14 hrs	2 hrs	9 hrs
RUN TIME <small>CR123A</small>	1.5 hrs	2.75 hrs	11 hrs	1.25 hrs	7.25 hrs

TEN-TAP® Programmable:

- White light high only/IR high only (default)
- White light medium only/IR high-low
- White light low-high/IR low-high

ITEM NUMBERS

Description	UPC	Item #
ProTac Rail Mount VIR Pro - Includes remote pressure switch, remote retaining clips, M-LOK® mount, mounting hardware and (2) CR123A lithium batteries - Black	080926-88138-9	88138
ProTac Rail Mount VIR USB Pro - Includes remote pressure switch, remote retaining clips, M-LOK® mount, mounting hardware, (1) SL-B26 battery pack and USB cord - Black	080926-88139-6	88139

KEY FEATURES

- Integrated IR to white light safety cutoff
- Mode selector switch for IR/Off/White light
- Integrated rail clamp attaches to MIL-STD-1913 (Picatinny) rail or M-LOK® compatible rails

BATTERY

- Multi-fuel: Uses one Streamlight SL-B26® protected Li-Ion rechargeable battery pack or two CR123A lithium batteries

MATERIAL/DURABILITY

- 6000 series machined aircraft aluminum with anodized finish
- High-temperature, shock-mounted, anti-reflective coated, impact-resistant BOROFLOAT® glass lens
- IPX7 waterproof 1m for 30 minutes with standard push-button switch installed
- IPX4 water-resistant with remote pressure switch installed

DIMENSIONS

LENGTH: 5.65 in (14.4 cm)

WEIGHT: CR123A 8.2 oz (231g) // SL-B26 8.8 oz (249g)
W/ BATTERIES

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information

	Description	UPC	Item #
	M-LOK® Mount	080926-88300-0	88300
	Jack-Cap®	080926-88130-3	88130
	Remote Retaining Clips	080926-88178-5	88178
	Straight Latching Pressure Switch	080926-89008-4	89008
	Straight Momentary Pressure Switch	080926-69135-3	69135
	CR123A Lithium Batteries - 2 Pack CR123A Lithium Batteries - 6 Pack CR123A Lithium Batteries - 12 Pack CR123A Lithium Batteries - 400 Pack	080926-85175-7 080926-85180-1 080926-85177-1 080926-85179-5	85175 85180 85177 85179
	SL-B26 Battery Pack - 1 Pack SL-B26 Battery Pack - 2 Pack SL-B26 Battery Pack - 8 Pack	080926-22101-7 080926-22102-4 080926-22105-5	22101 22102 22105
	USB-C Cord - 22" (55.88 cm)	080926-22084-3	22084
	8-Unit SL-B26 Bank Charger - 12V DC 8-Unit SL-B26 Bank Charger - 120V/100V AC 8-Unit SL-B26 Bank Charger - 230V/240V AC <i>Batteries not included</i>	080926-20220-7 080926-20221-4 080926-20222-1	20220 20221 20222
	8-Unit SL-B26 Bank Charger - 12V DC 8-Unit SL-B26 Bank Charger - 120V/100V AC 8-Unit SL-B26 Bank Charger - 230V/240V AC	080926-20223-8 080926-20224-5 080926-20225-2	20223 20224 20225
	SL-B26 Charger Kit	080926-22010-2	22010
	SL-B26 Charger Kit 120V AC	080926-22011-9	22011
	SL-B26 Charge Cradle	080926-22100-0	22100
	120V AC Micro-USB Charge Cord <i>for use with charge cradle</i>	080926-22071-3	22071
	230V AC Micro-USB Charge Cord <i>for use with charge cradle</i>	080926-22072-0	22072
	240V AC USB Wall Plug <i>for use with charge cradle</i>	080926-22049-2	22049

All rights reserved. M-LOK® is a registered trademark of Magpul Industries Corp.