

## ENGLISH

**IMPORTANT: FULLY DISCHARGE BATTERY PACK BEFORE BEGINNING REPLACEMENT.**

Read these instructions and watch the video in this QR code prior to changing the Wedge® XT battery.



## BATTERY SAFETY

**⚠ CAUTION** EXPLOSION RISK, BURN, AND FIRE HAZARD. FULLY DISCHARGE BATTERY PRIOR TO BEGINNING REPLACEMENT.

**⚠ CAUTION** EXPLOSION RISK, BURN, AND FIRE HAZARD. DO NOT DISASSEMBLE, CRUSH, SHORT CIRCUIT, HEAT ABOVE 140°F (60°C), OR DISCARD IN FIRE. USE ONLY WITH THE SPECIFIED STREAMLIGHT PRODUCTS. KEEP AWAY FROM CHILDREN. BATTERY MUST BE RECYCLED OR DISPOSED OF PROPERLY.

The Wedge® XT battery is recyclable. At the end of its useful life, under various country and state laws, it may be illegal to dispose of this battery in the municipal solid waste stream. Check with your local solid waste officials for details in your area for recycling options or proper disposal (In USA: RBRC).

## BATTERY REPLACEMENT

### Open the flashlight body:

Use the included hex wrench to remove the four screws on the body. Make sure the hex wrench is fully seated into the head before removing the screws. The screws are torqued during manufacturing and may take some force to loosen. Remove the top half of the body. Be careful not to remove any of the white thermal paste which helps heat dissipate from the heatsink to the body.

### Open the battery compartment:

Use the tweezers to separate the seal (clear plastic cover) from the battery compartment to gain access to the battery. Use caution to avoid straining the wires connecting the battery to the flashlight.

### Remove the battery:

Carefully remove the battery from the flashlight and pay attention to how the wires are connected to the circuit board. Gently grip the wires using the included plastic tweezers and pull the battery connector toward the lens to remove from circuit board.

### Prepare the sealing surface:

Once the battery is removed, clean the surface for the replacement cover. Use the plastic tweezers to scrape any adhesive from the sealing surface on the battery compartment.

### Replace the battery:

Following the steps above in reverse with the replacement battery, use the tweezers to attach the battery connector to the circuit board. Note that the red wire should be facing up. Proper alignment is important for the connection to be made. **DO NOT FORCE.** The connector is keyed and will not allow incorrect orientation. Once the connection is made, the battery can be placed into the compartment. Ensure that wires are seated fully in the battery compartment.

### Seal the battery compartment:

Remove the adhesive protectors from both the replacement seal and battery adhesive. Carefully place the seal such that it aligns with the sealing surface on the battery compartment and battery. Once properly aligned, press around the perimeter and along the adhesive strip on the battery to ensure good contact is made.

### Reassemble the flashlight body:

Replace the other half of the flashlight body. Use the hex wrench to tighten the four screws. Torque hand tight. Fully charge battery prior to next use.

## SERVICE OPTIONS

For additional service options, go to [streamlight.com/support/service](http://streamlight.com/support/service) and complete the Online Service Request for factory service or to find the location of an authorized Streamlight repair center near you.

## Or contact:

Customer Service  
© Streamlight, Inc.  
30 Eagleville Road  
Suite 100  
Eagleville, PA 19403-3996, USA  
Phone: (800) 523-7488 Toll-Free /  
+1 (610) 631-0600  
Fax: (800) 220-7007 / +1 (610) 631-0712  
Email: [cs@streamlight.com](mailto:cs@streamlight.com)

---